## Mohawk Applied Moldings Standard Plant-On Profiles



## **Mohawk Applied Molding Designer Series**

This program gives design professionals outstanding design flexibility and the opportunity to enhance the beauty of the opening by adding applied molding. This stile and rail likeness on one or both sides elevates the flush door to the level of fine millwork at a fraction of the cost of stile and rail products.

We offer seven standard molding profiles and four standard plant-on design elevations (MP2, MP3, MP4, and MP6). Your design options do not stop here as we have the capabilities to custom-design your choice of molding profiles and layouts.

This program does not compromise your lead-time as it only adds one week for standard and two weeks for custom profiles and layouts. These lead-times include prefinished molding and machining, and each door is polywrapped to protect it against the job site environment.

Our standard wood species is basswood; all other species by special request. Our standard plant-on configurations have 6" stiles, 6" top rail, and 10" bottom rail after prefitting. These plant-ons are attached by mechanical fasteners.

Decorative moldings may be applied to fire doors with the following restrictions: Standard or custom profiles, maximum width 2-1/2", maximum height 3/4".

Multiple pieces may be used providing the pieces are separated with a space between the pieces of no less than the width of the individual piece. Must be a minimum of 4" from edge of door or lite. Maximum area of molding not to exceed 22% of the area of the door.

Example: 3/0 x 7/0 door with 1-1/2" molding, maximum usage is 443-1/2 lineal inches. Note that all of our standard profiles qualify for fire door applications.

To prevent warpage, balanced construction is required. Applied molding must be applied to two sides and of the same configuration to maintain manufacturer's warranty.



